Futura HPL

European Birch plywood finished on both faces with a hard-wearing high pressure laminate produced by Egger in Germany. The fine Birch veneer lay-up provides an attractive edge detail.

Futura HPL comes in a great range of colours and woodgrains.

DIMENSIONS

2440 x 1220mm	18mm/13ply	24mm/17ply	35mm/25ply
White	 Image: A second s	1	1
Porcelain	 Image: A start of the start of	 Image: A second s	
Taupe Grey	 Image: A second s	 Image: A second s	
Stone Grey	√	 Image: A second s	
Lava	 Image: A second s	 Image: A second s	
Black	√	 Image: A second s	√
Saffron	 Image: A second s		
Wasabi	 Image: A second s		
Denim	 Image: A second s		
Carini Walnut	 Image: A second s		
Mandal Maple	 Image: A second s		
Sorano Oak	√		



POWERED BY GREEN

Manufactured using electricity produced from 100% renewable energy sources with official guarantees of origin.

PERFORMANCE

Environment Protection Standard: ISO 14001:2005

Quality Management Standard: ISO 9001:2009

FSC & PEFC Certified

TECHNICAL SPECIFICATIONS

Standard – EN 636-2

Wood Raw Material – European Birch

Density – average 700kg/m3

Class – Hardwood, non-durable

Glue Bond – EN 314-3: Class 2 Exterior

Riga ECOlogical: Bio-based and renewable lignin glue system for safer living and working environments.

SCOPE OF USE

High-end joinery and furniture. Office and shop fittings.

LIMITATIONS ON USE

For interior use only.

EDGING

Because the core is free of voids and is birch throughout, the exposed edges give a unique edge detail. No need to spend time and effort on applying edge tape or solid edge banding unless you want to. Simply sand and finish the edges.

HANDLING AND STORAGE

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat.

Avoid leaning sheets against walls. Store sheets where construction traffic and construction activity will not damage sheets. Keep the surface free of contaminants such as dust, oil and adhesives that will affect the surface finishes.

The storage area should be protected from sun, rain and wind to minimise rapid changes in temperature and humidity. Treat sheets as a finished product and avoid dragging sheets across other surfaces.

Panels are always to be handled by two people.



PLYTECH SHOWROOM

26 Business Parade North, PO Box 204-070, Highbrook, Auckland 2161, New Zealand. Phone: 09 573 5016, Fax: 09 573 5035

sales@plytech.co.nz

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade.





Mandal Maple