



Photo @ Samoan Consulate by Walker Community Architects

Gaboon B/BB

Manufactured from 100% Okoume hardwood logs. The Gaboon B/BB grading allows for generally, good quality face veneers suitable for staining or clear finishing. The application of a clear coat enhances the natural warmth of the grain and colour of the Okoume veneer. For a superior finish, check out Joubert Gaboon.

KEY FEATURES

- Generally pale pink to brown in colour with a straight to slightly wavy grain and an even medium texture.

DIMENSIONS

2500 x 1220mm – 4mm/3ply, 6mm/5ply, 10mm/5ply, 12mm/7ply, 15mm/9ply, 18mm/11ply, 22mm/13ply, 25mm/11ply

Jumbo size (Eucalypt core) 3100 x 1530mm – 10mm/7ply, 12mm/7ply, 15mm/9ply, 18mm/11ply

SCOPE OF USE

Commonly used for walls and ceilings, as well as multiple applications in the furniture and joinery industries.

PERFORMANCE

FSC Certified

PEFC Certified.

TECHNICAL SPECIFICATIONS

Standard – Marine Bonded Exterior

Wood Raw Material – Okoume

Density – average 520kg/m³

Class – Hardwood, non-durable

Glue Bond – Class 3 Exterior Glue
EN314-1,2

Formaldehyde Emissions – E1

COLOUR CONSISTENCY

It is not possible to guarantee an absolute consistency in colour of plywood between sheets. A slight variation between sheets cannot be considered a defect. Check sheets before commencing your project.

EXPOSURE TO WATER AND SUNLIGHT

Direct or indirect light will have an effect on plywood products. A change in colour and appearance over time is a natural charactersitic, not a defect.

HANDLING AND STORAGE

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat.

Avoid leaning sheets against walls. Store sheets where construction traffic and construction activity will not damage sheets. Keep the surface free of contaminants such as dust, oil and adhesives that will affect the surface finishes.

The storage area should be protected from sun, rain and wind to minimise rapid changes in temperature and humidity. Treat sheets as a finished product and avoid dragging sheets across other surfaces.

Panels are always to be handled by two people.



PLYTECH SHOWROOM

26 Business Parade North, PO Box 204-070, Highbrook, Auckland 2161, New Zealand. Phone: 09 573 5016, Fax: 09 573 5035

sales@plytech.co.nz

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade.

The "plytech" logo is written in a bold, lowercase, orange font with a slightly irregular, hand-drawn style.