



Plytech Meranti BS1088

Plytech Meranti BS1088 is manufactured from high quality hardwood logs and is known for its natural durability, strength and stability. The face veneers of Meranti BS1088 are rotary cut and feature an attractive bold grain and a fine multi-ply edge detail.



Applications:

Boat building: hull, decks and interior joinery
 High-end furniture and joinery
 Wall and ceiling lining.

Features:

Meranti BS1088 Heartwood varies in colour from pale pink to red-brown with interlocked, wavy grain and a coarse but even texture.

Technical Specifications:

Standard – EN 636-3
 Faces – AB/B
 Wood Raw Material – Indonesian hardwood
 Density – average 650kg/m³
 Class – Hardwood, moderately durable
 Glue Bond – A Bond Exterior
 Glue Formaldehyde Emission – E1.

Environment:

Environment Protection Standard: ISO 14001:2005
 Quality Management Standard: 13986: 2004
 Glue formaldehyde emissions: CARB - Phase 2
 LVLK Certification.

Dimensions:

2440 x 1220mm (Length x Width)
Thickness
4mm/3ply, 6mm/5ply, 9mm/7ply, 12mm/9ply, 15mm/11ply, 18mm/13ply, 25mm/17ply

Handling and Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free standing kitchen/ cabinet doors are concerned.

For further information contact us on **0800 900 905**

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade. Please contact us for further detailed information.

