

# Plytech Plycil

*Plytech Plycil is manufactured from renewable plantation grown NZ Radiata Pine and meets NZ Building Codes according to AS/NZS 2269. Plytech Plycil is overlaid on both faces with a phenolic resin impregnated paper overlay providing an excellent surface for painting. Designed for use as window reveals and sills, especially those that are 150mm or wider. Plytech Plycil is treated to H3.1 to withstand moisture build-up from condensation.*



## Applications:

Window reveals and sills.

## Features:

Plycil features a brown resin impregnated paper overlay on both sides.

## Technical Specifications:

Standard – AS/NZS 2269  
Wood Raw Material – Pinus Radiata  
Density – average 500kg/m<sup>3</sup>  
Class – Softwood, non-durable  
Glue Bond – A Bond Exterior  
Glue Formaldehyde Emissions E0 < 0.5mg/L (AS/NZS 2098.11).

## Environment:

E0: No harmful emissions.

## Dimensions:

Thickness	Length x Width
19mm	2400 x 1200mm

## Handling and Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free standing kitchen/ cabinet doors are concerned.

For further information contact us on **0800 900 905**

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade. Please contact us for further detailed information.

**plytech**  
CREATIVE STRENGTH