



Caravan Interior Panelling

Applications:

Lightweight pre-finished panels for lining and construction of furniture components for caravans, motor homes, campers, buses and transportable homes.

Technical Specifications:

Wood Raw Material – Mixed Indonesian Hardwood
 Density – average 600kg/m³
 Class – Hardwood, moderately-durable
 Glue Bond – Interior Moisture Resistant
 Glue Formaldehyde Emissions – E1.

Effect of Moisture:

Although Caravan and Polyply are moisture resistant panels, we don't recommend that panels be installed in applications which are subject to prolonged direct water contact.

Fastening:

Wallboard adhesive should be applied to the framing or existing wall surface in continuous beads in accordance with manufacturers' recommendation. Fresh framing timber should have a moisture content of less than 24%. Nail fixing with fine panel pins gently flushed to the ply surface may be necessary in some installations. Careful colour matching of pin heads may or may not be needed depending on the pattern of ply used.

Jointing:

Wallboard jointing extrusions in plastic or aluminium are normally used. Plytech offer an Ezy-Press two piece H-jointing extrusion that can fit both 3mm and 3.6mm Caravan and Polyply panels for easy installation.

Dimensions:

2440 x 1220mm (Lenght x Width)
White Anti Scratch, White Leather
3mm
Self-Adhesive Tapes
White Anti Scratch
50 lineal metres x 15mm width
Ezy-Press
Base & Cap panel joiners plain white
Sold per set 2450mm lenght

Maintenance:

The surface is readily cleaned with a soft cloth and soapy water. Ammonia based, solvent or abrasive cleaning agents can damage the surface and should be avoided.

Handling And Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free standing kitchen/cabinet doors are concerned.



PLYTECH SHOWROOM

26 Business Parade North, PO Box 204-070, Highbrook, Auckland 2161, New Zealand. Phone: 09 573 5016, Fax: 09 573 5035

sales@plytech.co.nz

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade.

